

## ROCKCOTE EcoStyle Ceiling White

ROCKCOTE EcoStyle Ceiling White is a premium quality, water-borne ceiling paint that is user friendly & environmentally friendly. Suitable for interior application only, ROCKCOTE EcoStyle Ceiling White is an emulsion based product providing maximum adhesion to most surfaces and drying to a tough flat finish. This ultra Low V.O.C. (Volatile Organic Compound) paint is ideal for users who are health conscious and concerned about environmental air pollution and indoor air quality. Areas painted with ROCKCOTE EcoStyle Ceiling White have no lingering paint fumes.

ROCKCOTE EcoStyle Ceiling White is made from high grade components and provides excellent opacity.

### PERFORMANCE & PROPERTIES

- Environmentally friendly paint manufactured without the use of VOC's [Volatile Organic Compounds] or dangerous chemicals.
- Low odour, does not release toxic fumes either during or after application.
- Stylish flat finish available in a wide range of pale decorative colours.
- Water-Borne product ensures easy application and clean up, very low roller spatter.
- Areas painted with EcoStyle Ceiling White have no lingering paint fumes.

### Composition

ROCKCOTE EcoStyle Ceiling White is composed of special new generation binder not requiring VOC solvents with titanium dioxide pigment and quality mineral extenders

### Typical Uses

ROCKCOTE EcoStyle Ceiling White is for use on ceilings.

### Limitations

- Not for use over powdery unbound or loose surfaces.
- For interior use only.
- Not suitable for areas that may be submerged in water or subject to continual damp.

### SURFACE PREPARATION

Ensure the surface is free from loose material, clean, dry and free from oil and grease. Sand any non porous surfaces such as glossy painted areas. Patch and fill holes and cracks with ROCKCOTE Sanding Patch.

For best results, sand the area to be coated to give an even finish before painting. Do not sand the paper surface of plasterboard.

Pre-coat any absorbent plaster joints with ROCKCOTE EcoStyle Sealer/Undercoat.

Remove all mould, mildew or fungi and treat these areas with ROCKCOTE Fungicidal Wash. ROCKCOTE EcoStyle Ceiling White does not support the growth of mould mildew or fungi.

### Previously Painted:

- Best results are obtained with the application of one coat of ROCKCOTE EcoStyle Sealer/Undercoat.

### Plaster Board (Paper Covered):

- Apply one coat ROCKCOTE EcoStyle Sealer/Undercoat then one or two coats of ROCKCOTE EcoStyle Ceiling White.

### Cement and Fibre Cement Sheeting:

- Apply one coat ROCKCOTE EcoStyle Sealer/Undercoat then one or two coats of ROCKCOTE EcoStyle Ceiling White.

### Timber and Hardboard:

- Apply one coat ROCKCOTE EcoStyle Sealer/Undercoat then one or two coats of ROCKCOTE EcoStyle Ceiling White.

## APPLICATION

- Thoroughly stir contents before use.
- Can be applied by brush, roller or spray. ROCKCOTE EcoStyle Ceiling White goes on with a minimum of roller spatter. For best results, use a 9-10mm synthetic sleeve.
- Do not apply if the temperature is below 3°C or is likely to fall below 3°C when drying.

Colour	White (Can be tinted)
Thinning	Can be thinned up to 5% Volume with water
Clean Up	Water. Recently dried material can be removed with methylated spirits
Dry Time	Touch dry in 20 minutes. Dry to recoat in 2 hours depending on temperature and humidity.
Pail Size	1lt, 4lt and 15lt
Finish	Flat
Durability	Excellent, interior only
Recommended film thickness per coat	71 microns (wet) gives 30 microns(dry)
Usual number of coats	2

The application of EcoStyle Ceiling White is a specialist procedure and should only be carried out by a skilled and experienced applicator.

## THEORETICAL COVERAGE RATES

14m<sup>2</sup> per litre, depending on substrate porosity and texture

NB: Figures are a guide only. Coverage rates vary according to application technique and substrate preparation.

## STORAGE, SAFETY & HANDLING

- Refer to ROCKCOTE MSDS for EcoStyle Ceiling White
- If you can't use your leftover paint give it to someone who can. Consider giving your paint to friends and neighbours or local community groups such as Scouts or charity groups undertaking community work.
- Residual small amounts of leftover paint on brushes and rollers should be wiped onto old newspaper and allowed to dry rather than being washed down the sink.
- Residual paint in the pail should be allowed to dry before disposal. Dried paint films should be disposed of in normal rubbish bins.
- Dried ROCKCOTE EcoStyle paint has very poor adhesion to the plastic pails it is sold in, so dried paint in the pail can normally be peeled off and the pail can be used for another use such as storing fishing tackle or garden tools. The pails are also approved for recycling by most municipal councils in Australia.
- ROCKCOTE EcoStyle Paint is suitable for disposal through the RA Industries Reclaimer Portable Paint Wash Recycling System.

### Indemnity

ROCKCOTE Enterprises Pty Ltd will not accept responsibility for any misuse of this product or if not applied by a skilled and experienced applicator and in accordance with our technical specifications. Due to our policy of continuing product improvement Rockcote Enterprises Pty Ltd reserves the right to change these specifications without further notice.